

SUNPROTECTION

PRODUCTLINE
NATURALS















PRODUCTTYPE
PVC free glass fibre fabric, halogen-free coating



PRODUCT NAME
0952 TECHNIC

Flocart glass fibre blinds let you enjoy the pleasant sunlight without getting your room overheated. Glass fibre being well known for its dimensional stability, flame retardant properties and durability. Flocart blinds are a durable solution that have been developed for intense use.

TECHNICAL SPECIFICATIONS

 Composition PVC free glass fibre fabric, halogen-free coating	 Dimensional stability variation < 0,5%
 Weight 180 gr/m ² (± 5%/m ²)	 Fire classification NF-P 92/507 (2004) – M1 • Din 4102-01 (May 1998) – A2
 Width 89 mm - 127 mm - 2050 mm – 2350 mm	 Lightfastness 6 - ISO 105 B02 (1999)
 Thickness 0,24 mm (± 5%)	 Heat sealable yes
 Usage vertical blind	 Care instructions wipe with a damp cloth
 Usage roller blind	 Thermal and optical factors DIN EN 410:2011-04

Reference		Solar Transmission %	Solar Reflection %	Solar Absorption %	Gtot double glazing with argon	UV Transmission %
01	POLAR	42,50	52,60	4,90	0,41	33,60
02	IVORY	41,37	50,10	8,53	0,41	29,70
03	DUNE	36,40	40,90	22,70	0,44	27,37
04	MAGNETIC	33,70	39,40	26,90	0,45	26,50
05	STEEL	28,60	32,53	38,87	0,47	23,23
06	LATTE	27,10	30,67	42,23	0,47	21,53
07	ROCK	21,23	21,57	57,20	0,50	18,07
08	MYSTIC	10,30	9,60	80,10	0,54	7,37
09	ASH	4,87	4,60	90,53	0,55	4,70
10	FOREST	14,57	15,20	70,23	0,52	9,37
11	CORAL	25,17	27,83	47,00	0,48	11,50
12	CORN	29,87	35,57	34,56	0,46	17,07
13	MAGNOLIA	41,10	49,90	9,00	0,41	28,73
14	KOALA	26,30	32,13	41,57	0,47	16,63

COLORS



TERMS & CONDITIONS - Slight color changes may occur from one production to another.

FLOCART - Zuidstraat 18, 8560 Wevelgem BE • T. +32 (0) 56 420 662 • info@flocart.com • www.flocart.com

PICTURE

