

SUNPROTECTION

PRODUCT LINE	PRODUCT TYPE	PRODUCT NAME
BLACKOUTS	Indoor roller blind fabric	07642 NOX
COMPOSITION	Glass fibre (PVC free) / Halogen-free coating + flock	
WEIGHT	525 g/m ² (± 5%/m ²)	
USAGE	Vertical blind / Roller blind	
WIDTH	89 mm - 127 mm - 2350 mm - 3200 mm	
ROLL LENGTH	Vertical blind: 50 m - Roller blind: 25 m	
THICKNESS	0,60 mm (± 5%)	
DIMENSIONAL STABILITY	Variation < 0,5%	
LIGHTFASTNESS	6 - ISO 105 B02 (1999)	
PROCESSING INSTRUCTIONS	cold cut - heat sealable with tape	
PRINTABLE	glass fabric side: latex + UV flock side: latex + UV	
CARE INSTRUCTIONS	Wipe with a damp cloth	
FIRE CLASSIFICATION	B1: DIN 4102-01 (1998) M1: NF P92-507 (2004)	
HYGIENIC PROPERTIES	anti-microbial ASTM E2180 anti-bacterial AATCC147	

MECHANICAL PROPERTIES

MECHANICAL RESISTANCE	BREAKING	TEAR	FOLDING
Warp	> 320 daN/5 cm	> 15 daN	> 320 daN/5 cm
Weft	> 200 daN/5 cm	> 20 daN	> 140 daN/5 cm
	ISO 1421-1 (2016)	EN 1875-3 (1997)	ISO 1421-1 (2016)
Elongation (warp and weft)	< 7% - ISO 1421-1 (2016)		

THERMAL AND OPTICAL FACTORS DIN EN 410:2011-04

REFERENCE	% SOLAR TRANSMISSION	% SOLAR REFLECTION	% SOLAR ABSORPTION	GTOT DOUBLE GLAZING WITH ARGON	% UV TRANSMISSION
01 POLAR	0	74,27	25,73	0,33	0
02 IVORY	0	74,00	26,00	0,33	0
03 DUNE	0	73,70	26,27	0,33	0
04 MAGNETIC	0	73,07	26,93	0,33	0
05 STEEL	0	72,33	27,67	0,33	0
06 LATTE	0	71,13	28,87	0,34	0
07 ROCK	0	73,53	26,47	0,33	0
08 MYSTIC	0	74,40	25,60	0,33	0
09 ASH	0	73,57	26,43	0,33	0
13 MAGNOLIA	0	73,93	25,97	0,33	0
14 KOALA	0	73,10	26,80	0,33	0



TERMS AND CONDITIONS

Slight color changes may occur from one production to another.

FLOCART - ZUIDSTRAAT 18, 8560 WEVELGEM, BELGIUM +32 (0) 56 420 662 - info@greenshade.be - www.greenshade.be