

SUNPROTECTION

PRODUCT LINE	PRODUCT TYPE	PRODUCT NAME
NATURALS	Indoor roller blind fabric	0952 TECHNIC
COMPOSITION	Glass fibre (PVC free) / Halogen-free finish	
WEIGHT	185 g/m ² (± 5%/m ²)	
USAGE	Vertical blind / Roller blind	
WIDTH	89 mm - 127 mm - 2000 mm - 2400 mm	
ROLL LENGTH	Vertical blind: 100 m - Roller blind: 50 m	
THICKNESS	0,24 mm (± 5%)	
DIMENSIONAL STABILITY	Variation < 0,5%	
LIGHTFASTNESS	6 - ISO 105 B02 (1999)	
PROCESSING INSTRUCTIONS	cold cut - heat sealable with tape	
PRINTABLE	latex + UV	
CARE INSTRUCTIONS	Wipe with a damp cloth	
FIRE CLASSIFICATION	A2: DIN 4102-01 (1998) M1: NF P 92-507 (2004)	

MECHANICAL PROPERTIES

MECHANICAL RESISTANCE	BREAKING	TEAR	FOLDING
Warp	> 100 daN/5 cm	> 4 daN	> 70 daN/5 cm
Weft	> 70 daN/5 cm	> 8 daN	> 20 daN/5 cm
	ISO 1421-1 (2016)	EN 1875-3 (1997)	ISO 1421-1 (2016)
Elongation (warp and weft)	< 5% - ISO 1421-1 (2016)		

THERMAL AND OPTICAL FACTORS DIN EN 410:2011-04

REFERENCE	% SOLAR TRANSMISSION	% SOLAR REFLECTION	% SOLAR ABSORPTION	GTOT DOUBLE GLAZING WITH ARGON	% UV TRANSMISSION
01 POLAR	42,50	52,60	4,90	0,41	33,60
02 IVORY	41,37	50,01	8,53	0,41	29,70
03 DUNE	36,40	40,90	22,70	0,44	27,37
04 MAGNETIC	33,70	39,40	26,90	0,45	26,50
05 STEEL	28,60	32,53	38,87	0,47	23,23
06 LATTE	27,10	30,67	42,23	0,47	21,53
07 ROCK	21,23	21,57	57,20	0,50	18,07
08 MYSTIC	10,30	9,60	80,10	0,54	7,37
09 ASH	4,87	4,60	90,53	0,55	4,70
13 MAGNOLIA	41,10	49,90	9,00	0,41	28,73
14 KOALA	26,30	32,13	41,57	0,47	16,63



TERMS AND CONDITIONS

Slight color changes may occur from one production to another.

FLOCART - ZUIDSTRAAT 18, 8560 WEVELGEM, BELGIUM +32 (0) 56 420 662 - info@greenshade.be - www.greenshade.be